

## TILES WORK NEAR TUCK SHOP

### Specification of Floor tiles

1. Using good quality tiles that are flat, true to shape, and free from cracks, chipped edges, and corners. Thickness of tiles/Kota stone 15mm
2. Preparing the base by cleaning it of dirt, scum, and loose materials, and wetting it without creating pools of water
3. Using a 1:4 mix of cement mortar for bedding
4. Setting tiles at right angles, and ensuring corners are not bent
5. Maintaining minimal joints between tiles, and wiping off excess joints

### Specifications for Kota stone:

**Thickness of** Kota stone 20–25 mm thick.

#### 1. **Laying the Stone:**

Apply a layer of cement mortar or adhesive on the prepared surface using a notched trowel. Place the Kota stone on the mortar/adhesive, pressing them firmly and ensuring they are properly aligned.

Use a rubber mallet to tap the tiles gently, ensuring they are firmly fixed in place and there are no air gaps.

Maintain consistent spacing between Stone using tile spacers.

#### 2. **Grouting:**

Once the Stone are set, allow them to dry and cure for a specific period according to the manufacturer's instructions.

Mix a grout of the desired color and consistency.

Apply the grout between the tiles using a grout float, pressing it into the gaps and ensuring they are completely filled.

Clean off any excess grout from the tile surface using a damp sponge.

#### 3. **Finishing:**

After the grout has dried, clean the entire surface to remove any remaining grout haze or residue.

Polish the Kota stone tiles using a buffing machine or polishing pads to enhance their natural shine and Kota Stone Design.

Apply a sealant or polish to protect the stone and improve its longevity.

4. **Color:** Kota stone color green or gray.

**Note: - Quote your rate including labour, transportation, installation and all taxes like GST etc. Visit the site / place before quoting your bid.**

Principal   
Army Public School  
Janglut (J&K)